

Material Lifts

Superlift Advantage™

Features

Standard Features

Measurements

SLA™ -5

- 6 ft 7 in (2.0 m) maximum lifting height
- Up to 1,000 lbs (454 kg) load capacity

SLA-10

- 11 ft 5.5 in (3.49 m) maximum lifting height
- Up to 1,000 lbs (454 kg) load capacity

SLA-15

- 16 ft 4 in (4.98 m) maximum lifting height
- Up to 800 lbs (363 kg) load capacity

SLA-20

- 21 ft 2.5 in (6.46 m) maximum lifting height
- Up to 800 lbs (363 kg) load capacity

SLA-25

- 26 ft .5 in (7.94 m) maximum lifting height
- Up to 650 lbs (295 kg) load capacity

Productivity

- Heavy-duty design
- Patented telescoping mast system
- Captive stabilizer set (standard on SLA-20, -25)
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Interchangeable load handling attachments
- Maneuverable 4 in (10 cm) front casters and 5 in (13 cm) rear casters, with 4-way swivel locks and side brakes
- Compact design, legs fold up for easy storage
- Easy to load and unload on or off a vehicle for transport
- Hold-down bar secures mast assembly during transport
- Winch locks load in place

Power

- One speed manual winch

Options & Accessories

Productivity & Fork Options

- Adjustable forks
- Fork extensions
- Flat forks (SLA-5, -10, -15 only)
- Boom
- Pipe cradle (available aftermarket only)
- Load platform
- Captive stabilizer set (option on SLA-5, -10, -15)
- Mast brake

Power Options

- Two-speed manual winch

Base Options

- Straddle base (SLA-5, -10, -15 only)
- Stabilizer set (standard on SLA-20, -25, not available on straddle base)

Caster & Brake Options

- Rear transport wheel assembly



Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By:

Effective Date: January, 2017. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2017 Terex Corporation.