


SPECIFICATIONS

Metric	British
18.00m	59ft 1in
16.00m	52ft 6in
4.88m	16ft
2.29m	7ft 6in
3.19m	10ft 6in
2.49m	8ft 2in
3.98m×1.83m	13ft 1in ×6ft
1.43m/1.16m	4ft 8in/3ft 10in
0.30m	1ft
2.86m	9ft 5in
2.35m/5.20m	7ft 9in/17ft 1in
33×12-20	33×12-20
	18.00m 16.00m 4.88m 2.29m 3.19m 2.49m 3.98m×1.83m 1.43m/1.16m 0.30m 2.86m 2.35m/5.20m

Performance		
S.W.L	680kg	1499lb
S.W.L On Extension	227kg	500lb
Max. Occupants (Indoor/Outdoor)	4	4
Gradeability	40%	40%
Travel Speed(Stowed)	6.0km/h	3.73mph
Travel Speed(Raised)	1.0km/h	0.62mph
Max. Working Slope	X-2°/Y-3°	X-2°/Y-3°
Up/Down Speed	80/70sec	80/70sec

Weight			
Overall Weight	8900kg	19621lb	

Power		
Hydraulic Tank	130L	34gal
Battery	48V/450Ah	48V/450Ah
Charger	48V/60A	48V/60A
Driving Motor	4×32VAC/3.3kW	4×32VAC/3.3kW
Lifting Motor	2×48VDC/8.0kW	2×48VDC/8.0kW







FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- Dual Slide-Out Platform Extension Deck
- Four-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Self-Weight Lowering System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Charging Indicator
- Manual Brake Release
- · Lanyard Attachment Point
- Standard Transport Forklift Pockets
- Tie-Down And Lifting Points
- Automatic Leveling Hydraulic Outriggers
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System
- Oscillating Axle Chassis



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Due to continuous technology updates, technical parameters are subject to change without notice. This picture

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











