

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor, 1.5 kW with thermal protection and minimum voltage coil
- ✓ IP 55 switch
- ✓ IP 67 plug
- ✓ Laser pointer
- ✓ Cutting guide
- ✓ Diamond blade Ø 250 mm PREMIUM for gres hard porcelain - continuous rim
- ✓ Protractor with large support surface
- ✓ Anodised extruded aluminium cutting surface
- ✓ Shatter-resistant plastic tray to contain and recover water
- ✓ Stand with two rubber wheels
- ✓ Side cutting surface
- ✓ Tile locking tool

Optional Accessories and recommended blades

- ✓ Side cutting surface
- ✓ Rip guide
- ✓ Tile locking tool
- ✓ Diamond blade Ø 250 mm PREMIUM for gres hard porcelain - continuous rim
- ✓ Diamond blade Ø 250 mm FLEX for ceramic - continuous rim

Applications

For a quality cut even on large tiles: 300x600 mm, 900x900 mm and over. Max. cutting length 1500 mm.

They offer high cutting capacity: the blade is suitable for all types of material to be cut. Cuts (90°) vertically to the support surface or cuts in tilted position between 90° and 45° (depth adjustment is maintained in all positions).

Side cutting surface allows to extend cutting, maintaining stability, due to a bracket bolted onto the stand. The machine can mount up to 2 side cutting surfaces and is shipped in a box with stand included.



TILE, MASONRY & SLABS SAWS

| COMBI 250-1500 VA | | |
|---|--------|--|
| Blade/bore diameter | Ø mm | 250/25.4 |
| Cutting length (with/without plunging blade 2 passes) | mm | 1430/1530 |
| Cutting depth 1 pass | mm | 66 |
| Cutting depth 2 passes | mm | 105 |
| Cutting surface dimensions | mm | 500x1615 |
| Electric power supply | V / Hz | 230 / 50 Sph 230 / 60 Sph 110 / 50 Sph 115 / 60 Sph |
| Motor power rate | kW | 1.5 |
| Motor speed | rpm | 2800 |
| Running current 230 V (110/115 V) | A | 9.4 (15.4) |
| Water pump | | IP67, flow rate 13 l/min |
| Water recovery tray capacity | l | 55 |
| Machine dimensions | mm | 636/1920/619 |
| Packing dimensions | mm | 669/1954/654 |
| Stand dimensions | mm | 545/1560/750 |
| Machine weight (with packing) | kg | 75 (91) |
| Stand weight | kg | 17 |
| Optional surface weight (with packing) | kg | 8.0 (8.6) |
| SPL in operator's position | dB(A) | 86 |
| Max. stackability* | | 3 (h 2190 mm) |

(* Number of stackable pieces and total height including pallet)



Handle for long cuts



OFF button incorporated in the handle



Standard protractor



Cutting at 45°



Standard laser pointer